



DOP

WATERPROOF BREATHING MEMBRANE TB-160

Waterightness, vapour permeable membrane - backed product for discontinuous roofing pitched roof. The products must be installed in accordance with manufacturer's instructions. Made by 3 layers of Polipropylene.



Harmonized standard:
EN 13859 - 1:2014 Flexible products for waterightness. Definitions and characteristics of underlays - Part 1: Underlays for discontinuous roofing.

The performance characteristics of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 the sole responsibility of the manufacturer's specified above.

DECLARATION OF PERFORMANCES			
CHARACTERISTICS	UNIT	PERFORMANCE	TOLERANCE
Reaction to fire	Clase	E	-
Resistance to water penetration	Clase	W1	-
Maximum tensile strength along	(N / 50 mm)	340	+30%
Maximum tensile strength across	(N / 50 mm)	250	+30%
Elongation along	(%)	80	+20%
Elongation across	(%)	120	+30%
Resistance to tearing (nail shank) along	(N)	200	+15%
Resistance to tearing (nail shank) across	(N)	260	+20%
Flexibility at low temperature	(°C)	-40	-
Artificial ageing	Resistance to water penetration	Clase	W1
	Maximum tensile strength (along/across)*	(N / 50 mm)	>80%
	Elongation (along / across)*	(%)	>60%
Complementary technical parameters	Mass per unit area	(g / m ²)	160
	Water vapor transmission properties	Sd (m)	0.02

*As percentage of the original value declared

Signature:

Fdo. Olmos
Product Manager

TEJAS BORJA, S.A.U.
C.I.F. A-46384764
Cr. Llíria a Pedralba, Km. 3
Teléfs. 96 279 80 14 - 96 279 80 15
46160 LLÍRIA (VALENCIA), ESPAÑA
Llíria (Valencia), 01 Abril de 2015