

DOP

MIXED RIDGE TAPE

Sealing and ventilation of the ridge and crests, protection against the negative influence of atmospheric conditions. The tape fulfils its ventilating function perfectly and protects from getting in rain and insects. The tape is made of lacquered aluminium resistant to ultraviolet radiation and polypropylene fabric.

Two strips of butyl glue enable easy and comfortable assembly to the roof tiles. The surface to be glued must be dry, clean and degreased for the installation.

Unroll the tape on the ridge batten, initially fasten the middle part with steel clips or nails, take off the protecting separator from the glue strips and carefully adjust the pleated sides to the shape of roofing.



#### DECLARATION OF PERFORMANCE

Material	Butyl rubber glue, polypropylene fabric and aluminium corrugated sheet gr. 120 µm
Width / Roll length	390 mm (+/- 3%) / 5000 mm (+/- 1%)
Thickness	120 µm (+/- 10%)
Air permeability	180 cm / sqm
Elongation	25 (+/- 5 %)
Butil Width	20 mm +/- 1
Outside temperature for installation	+ 5 °C
Temperature resistance	- 30 °C a + 80°C
Colors	Brick red, brown, black, beige

Signature:



Fdo. Olmos  
Product Manager



TEJAS BORJA, S.A.U.  
C.I.F. A-46384764  
Cr. Lliria a Pedralba, Km. 3  
Teléfs. 96 279 80 14 - 96 279 80 15  
46160 LLIRIA (VALENCIA) ESPAÑA  
Lliria (Valencia), 01 Abril de 2015